Technical data sheet

Junction box, B 10 M, with thread

Item number: 2002167





Protection rating IP54, rated voltage 660 V, nominal cross-section 2.5 \div 4, in combination with the earthing terminal 700/6 M, the box has the nominal crosssection 4 mm², two fastening holes for screws of up to 5 mm \varnothing on the outer side of the box. Four cover screws, 7 break-out entries with thread M20 x 1.5, primarily for cable glands with short connecting thread.

Clear internal dimensions: 80x80x39 mm.

B 10/4 M VDE: with five-pole earthing terminal 700/4 BM made of melamine for max. four 2.5 mm² cables per terminal

















Duroplast, Aminoplast

Master data		
	Item number	2002167
	Description 1	Junction box
	Manufacturer	OBO
	Dimension	91x91x51
	Colour	Light grey; RAL 7035
	Material	Duroplast, Aminoplast
	Smallest sales unit	5
	Unit of quantity	Piece
	Weight	14.533 kg
	Weight unit	kg/100 pc.

Technical data sheet


Junction box, B 10 M, with thread





Dimensions 42.3

Length	91 mm
Width	91 mm
Height	51 mm



Technical data

E and abla		
Expandable	no	
No. of entries	7	
Type of insertion	Gland	
Type of entry	Cable	
Type of housing penetration	Thread and pre-marking	
Measured insulation voltage Vi	660 V	
Cover	Not transparent	
Cover fastening	Screwed	
Entry from rear	no	
Entries	7 break-out entries with thread M20 x 1.5	
Explosion-tested version	no	
Flame-resistant	Acc. to VDE 0471/DIN 695 Part 2-1, test temperature 750°C	
Shape	Square	
Maintain electrical functions	Without	
For Ex zone	Without	
For Ex zone gas	Without	
For Ex zone dust	Without	
for pipe diameter	20 mm	
Halogen-free	yes	
Clear internal dimensions	80x80x39 mm	
With screening	no	
with lid	yes	
Nominal cross-section, max.	4 mm²	
Nominal cross-section, min.	2.5 mm²	
Nominal voltage	660 V	
Sealable	yes	
Impact-resistant	no	
	1	

Technical data sheet Junction box, B 10 M, with thread



Item number: 2002167

Technical data		
	Protection rating	IP54
	Weatherproof	no
	Junction box cover version	Blanking lid