Technical data sheet

GES4 service outlet with locking slider


Item number: 7405145



Service outlet with locking slider for up to 6 individual Modul 45 devices in 2 UT3 universal supports, use in trunking systems and system floors in indoor areas.

Floor covering recess in the hinged cover pre-adjusted to 5 mm, if necessary adjustable to 3, 8 or 10 mm.

Up to 4 installation devices can be used with 50 mm central plate.



Floor covering recess in the hinged cover pre-adjusted to 5 mm, if necessary adjustable to 3, 8 or 10 mm.





PA

Polyamide

Master data

Item number 7405145 Type GES4-2U10T 7011 Description 1 Service outlet Description 2 for universal mounting Manufacturer OBO Dimension 222x222x65 Colour Iron grey; RAL 7011 Material Polyamide Smallest sales unit 1 Unit of quantity Piece Weight Il4 kg		
Description 1 Service outlet Description 2 for universal mounting Manufacturer OBO Dimension 222x222x65 Colour Iron grey; RAL 7011 Material Polyamide Smallest sales unit 1 Unit of quantity Piece Weight 114 kg	Item number	7405145
Description 2 for universal mounting Manufacturer OBO Dimension 222x222x65 Colour Iron grey; RAL 7011 Material Polyamide Smallest sales unit 1 Unit of quantity Piece Weight 114 kg	Туре	GES4-2U10T 7011
Manufacturer OBO Dimension 222x222x65 Colour Iron grey; RAL 7011 Material Polyamide Smallest sales unit 1 Unit of quantity Piece Weight 114 kg	Description 1	Service outlet
Dimension 222x222x65 Colour Iron grey; RAL 7011 Material Polyamide Smallest sales unit 1 Unit of quantity Piece Weight 114 kg	Description 2	for universal mounting
Colour Iron grey; RAL 7011 Material Polyamide Smallest sales unit 1 Unit of quantity Piece Weight 114 kg	Manufacturer	OBO
Material Polyamide Smallest sales unit 1 Unit of quantity Piece Weight 114 kg	Dimension	222x222x65
Smallest sales unit 1 Unit of quantity Piece Weight 114 kg	Colour	Iron grey; RAL 7011
Unit of quantity Piece Weight 114 kg	Material	Polyamide
Weight 114 kg	Smallest sales unit	1
· ·	Unit of quantity	Piece
Weight unit kg/100 no	Weight	114 kg
vveight unit kg/100 pc.	Weight unit	kg/100 pc.

Technical data sheet

GES4 service outlet with locking slider



Technical data



Dimensions Length Width 2222 mm Height 65 mm

Number of installable devices	6	
Number of mounting boxes	2	
Version for	Square	
Cable outlet version	Swivellable cord outlet	
Floor covering protection frame	yes	
Floor care	Dry	
Seal installation option	no	
Screed height, min.	73 mm	
Floor height, min.	73 mm	
Suitable for raised floor installation	yes	
Suitable for screed-flush closed underfloor ducts	no	
Suitable for screed-covered underfloor ducts	yes	
Suitable for cavity floor installation	yes	
Suitable for wet care	no	
Suitable for underfloor box	250/350	
Suitable for underfloor ducts	yes	
Device support to accept mounting boxes	yes	
Length of external dimensions	222 mm	
Length of installation dimensions	201 mm	
With floor covering recess	yes	
Nominal size for device installation units	4	
Frame version	Carpet protection frame	
Protection rating (IP) when used	IP20	
Protection rating (IP) when unused	IP40	
Protection rating IK code	IK08	
Heavy-duty version	no	
Installation system type	UT3	

Technical data sheet

GES4 service outlet with locking slider

Item number: 7405145



Technical data		
	Vertical load, large area	to 5,000 N
	Vertical load, small area	to 3,000 N
	Approvals	VDE
	Opening mechanism	Locking slider
	Floor covering thickness	5 mm