

Technical data sheet

UTC4 W with 2+1 protective contact sockets

Item number: 7404623



The ready-for-connection UTC4 universal support has 2 pre-installed 33° protective contact sockets in orange and one pre-installed 33° protective contact socket in mint green and one blanking cover for retroinstallation of an installation device of the Modul 45 or Modul 45connect series, 250 V~, 16 A.

PVC connection cable with connector, 3-pin, type WINSTA® MIDI. Suitable for VL connection cables and device installation units of nominal size R7, R9 and 9. The ready-for-connection UTC4 universal support has 2 pre-installed 33° protective contact sockets in orange and one pre-installed 33° protective contact socket in mint green and one blanking cover for retroinstallation of an installation device of the Modul 45 or Modul 45connect series, 250 V~ 16 A.

PVC connection cable with connector, 3-pin, type WINSTA® MIDI



PA Polyamide

Master data

Item number	7404623
Description 1	Universal supportConnectWINSTA
Description 2	VDE, double white,single green
Manufacturer	OBO
Dimension	208x76x45
Material	Polyamide
Smallest sales unit	1
Unit of quantity	Piece
Weight	43.8 kg
Weight unit	kg/100 pc.


Technical data sheet

UTC4 W with 2+1 protective contact sockets

Item number: 7404623



Dimensions



Length	218 mm
Width	76 mm
Height	60 mm

Technical data

Connection cable, halogen-free	yes
Number of installable devices	4
Version for	Double pure orange/single mint green
Cable length	300 mm
Line cross-section	2.5 mm ²
Plug-in system	WINSTA® MIDI
Plug connector system, system-specific	yes
Circuit	2
System length	208 mm
Surge protection	no