

Technical data sheet

Plug-in arrester V10 385 V

Item number: 5093406



Surge arrester, type 2+3 to EN 61643-11

- Plug-in upper part; upper part can be separated from base without tools
- Incl. thermal and dynamic cut-off unit and visual display of defects
- High current conductivity and long service life



Master data

Item number	5093406
Type	V10-C 0-385
Description 1	SurgeController V10
Description 2	plug-in arrester
Manufacturer	OBO
Dimension	385V
Smallest sales unit	30
Unit of quantity	Piece
Weight	3.63 kg
Weight unit	kg/100 pc.


Technical data sheet

Plug-in arrester V10 385 V

Item number: 5093406



Technical data



Arrester surge current (8/20 μ s) [total]	10 kA
Response time	<25 ns
Version for	1-pole
Pole version	1
Structural width in division units (division unit, 17.5 mm)	1
Operating temperature, max.	80 °C
Operating temperature, min.	-40 °C
Maximum continuous voltage AC	385
Conductor cross-section, rigid (single-wire/multiwire), max.	35 mm ²
Conductor cross-section, rigid (single-wire/multiwire), min.	2.5 mm ²
Lightning protection zone LPZ	1→3
Max. mains-side overcurrent protection	125
Maximum back-up fuse	125 A
Maximum discharge current (8/20 μ s)	20 kA
Installation type	On basic element
Nominal discharge current (8/20 μ s)	10 kA
Nominal voltage AC (50/60 Hz)	385 V
Network form	All
Protection rating	IP20
Protection level	≤1,5
Signalling on device	Visual
SPD to EN 61643-11	Type 2+3
SPD to IEC 61643-1	Class II+III