

3+ NPE 385 V

: 5094788



- 2
-
- TN TT
-
- SPD
-
-
-

*=



Type 2 LPZ 1→2 FS

| | |
|---|-----------------|
| | 5094788 |
| | V20-C 3+NPEFS38 |
| 1 | V20 |
| 2 | 3+1 |
| | OBO |
| | 385V |
| | 1 |
| | 45.2 kg |
| | kg/100 |

3+ NPE 385 V

: 5094788

| | | |
|-----------------|------------------|---------------------|
| | (8/20 μ s) □ | 80 kA |
| | | <25 ns |
| | | 3+NPE |
| | | 3+N/PE |
| | (TE17.5mm) | 4 |
| | | 80 °C |
| | | -40 °C |
| | AC | 385 |
| | | 25 mm ² |
| | / | 35 mm ² |
| | / | 2.5 mm ² |
| | LPZ | 1→2 |
| | | 125 |
| | | 125 A |
| | (8/20 μ s) | 40 kA |
| | 35mm | |
| (8/20 μ s) | 20 kA | |
| AC (50 / 60 Hz) | 350 V | |
| | | |
| 2 | | |
| | IP20 | |
| | ≤1,7 | |
| | | |
| SPD EN 61643-11 | 2 | |
| SPD IEC 61643-1 | II | |