

# Technical data sheet

## Combination arrester V25, 3-pole + NPE 385 V

Item number: 5094478



Combination arrester, lightning and surge arrester type 1+2

- Complete unit consisting of upper part and base, pre-mounted and ready for connection
- Universally suitable for TN-S and TT systems
- Plug-in arrester with dynamic cut-off unit
- Visual function display
- Voltage protection level < 1.5 kV
- Encapsulated, non-extinguishing zinc oxide varistor arrester for use in standard distributor housings
- Labelled connections

Application example: Buildings with open-wire power supply or for setting up lightning protection equipotential bonding in residential buildings.

\* Complete = Plug-in arrester and base



### Master data

Item number	5094478
Type	V25-B+C 3NPE385
Description 1	CombiController V25
Description 2	3+1 version
Manufacturer	OBO
Dimension	385V
Smallest sales unit	1
Unit of quantity	Piece
Weight	53.7 kg
Weight unit	kg/100 pc.


# Technical data sheet

## Combination arrester V25, 3-pole + NPE 385 V

Item number: 5094478



### Technical data



Arrester surge current (8/20 $\mu$ s) [total]	120 kA
Response time	<25 ns
Blow-out	no
Version for	3-pole with NPE; 385 V
Pole version	3+N/PE
Structural width in division units (division unit, 17.5 mm)	4
Operating temperature, max.	80 °C
Operating temperature, min.	-40 °C
Lightning surge current (10/350 $\mu$ s)	7 kA
Lightning surge current (10/350 $\mu$ s) [N/PE]	25 kA
Lightning surge current (10/350 $\mu$ s)	25 kA
Remote signalling	no
Maximum continuous voltage (N-PE)	255 V
Maximum continuous voltage AC	385
Maximum continuous voltage DC	505
Conductor cross-section, rigid (single-wire/multiwire), max.	35 mm <sup>2</sup>
Conductor cross-section, rigid (single-wire/multiwire), min.	2.5 mm <sup>2</sup>
Lightning protection zone LPZ	0→2
Max. mains-side overcurrent protection	160
Maximum back-up fuse	160 A
Maximum discharge current (8/20 $\mu$ s)	50 kA
Nominal discharge current (8/20 $\mu$ s)	30 kA
Nominal discharge current (8/20 $\mu$ s) [L-N]	30 kA
Nominal discharge current (8/20 $\mu$ s) [N-PE]	30 kA
Nominal voltage AC (50/60 Hz)	350 V
Network form	Other
TN network form	yes
TN-C-S network form	yes
TN-S network form	yes
TT network form	yes
Pole number	3
Protection rating	IP20
Protection level	$\leq 1,6$
Protection level [L-N]	$\leq 1,6$
Protection level [N-PE]	1.2 kV
Signalling on device	Visual
SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-1	Class I+II