

Technical data sheet


3-wire connection cable, PVC, cross-section 2.5 mm², 1 m length, white

Item number: 6108712



Connection cable 3 x 2.5 mm² in the version socket-connector, type WINSTA® MIDI.

PVC hose pipe: H05VV-F 3 x 2.5 mm²
Suitable for connection of ready-for-connection universal supports Connect UTC to an energy distributor.



PA Polyamide

Master data

Item number	6108712
Type	VL-WIN 3P2.5 1W
Description 1	Connection cable
Description 2	3x2,5mm ² , WINSTA
Manufacturer	OBO
Dimension	1000x27x15
Colour	White
Material	Polyamide
Smallest sales unit	1
Unit of quantity	Piece
Weight	17.82 kg
Weight unit	kg/100 pc.

Technical data

Number of poles	3
Type of terminated cable	Connection cable
Type of locking	Separate
Version, page 1	socket
Version, page 2	Connector
Rated surge voltage	4
Fire load	0.88

Technical data sheet

3-wire connection cable, PVC, cross-section 2.5 mm², 1 m length, white

Item number: 6108712



Technical data

Colour of the coding/contact insert	White
Halogen-free	no
Cable type	H05VV-F
Cable length	1000 mm
Jacket colour	White
Mechanical encoding	yes
Nominal voltage	250 V
Nominal current	20 A
Pin labelling	L, N, PE
Cross-section	1.5 mm ²
Protection rating	IP20
Degree of soiling	3